

46-700 Differentiating characteristics of power steering pump

Part No.	Version	Opening pressure Pressure relief valve (bar gage pressure)	Color code Type rating plate	Installed in model	Remarks
127 460 12 80	without tank	65 ± 5	black	107 1st version ^{1) 2)}	Grey iron (Vickers VT 27)
116 460 17 80 116 460 20 80	with cast-on tank	65 ± 5	black	123, 1st version 107, 2nd version ^{1) 2)}	Grey iron (Vickers VT 49, ZF)
116 460 24 80 116 460 26 80	with cast-on tank	65 ± 5	black	123, 2nd version 107, 3rd version ¹⁾	Light alloy (Vickers VT 49, ZF)
126 460 00 80 126 460 02 80	with cast-on tank	65 ± 5	black	107, 4th version ²⁾	Light alloy (Vickers VT 49, ZF)
116 460 25 80 116 460 27 80	with cast-on tank	82 ± 5	blue	126 ¹⁾	Light alloy (Vickers VT 49, ZF)
126 460 01 80 126 460 03 80	with cast-on tank	82 ± 5	blue	126 ²⁾	Light alloy (Vickers VT 49, ZF)
201 460 05 80 201 460 06 80 201 460 09 80	with cast-on tank	65 ± 5	black	201.1, 02 ³⁾	Light alloy (ZF Vickers VT 60)
201 460 16 80	with cast-on tank	85 ± 5	blue (with green dash adjacent to type rating plate)	201.03 ³⁾	Light alloy (Vickers VT 60)

¹⁾ With engine 110

²⁾ With engine 116 and 117

³⁾ When a pump is replaced, make sure that only a pump with the same opening pressure will be installed.